

主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

| | | |
|-----------------|-----------------------------|----------------|
| China (PCEC Ex) | Ex e II C Gb DIPA21 | GB3836 GB12476 |
| IECEX | Ex e II C Gb Ex tb III C Db | IEC60079 |
| ATEX | Ex e II C Gb Ex tb III C Db | EN60079 |

适用范围: 用于 1 区和 2 区

Intended use: Can be used in zone 1 and zone 2

用于 21 区和 22 区

Can be used in zone 21 and zone 22

 使用环境温度: $-40^{\circ}\text{C} < \text{Ta} < 80^{\circ}\text{C}$

 Ambient temperature: $-40^{\circ}\text{C} < \text{Ta} < 80^{\circ}\text{C}$

防护等级: IP66

Degree of protection: IP66

材 料: 铜制表面镀镍

Material: nickel plated brass

订购规格 Order specifications:

 CZ0227 金属电缆密封套
 CZ0227 Metal cable glands

| 图样 Illustration | 编码 Code | 入口螺纹 Entry thread | 电缆直径 Cable diameter | G | L _{max} | L1 | L2 | SW | 订购号 Order No. |
|--------------------|------------|----------------------|------------------------|-------|------------------|----|----|----|-------------------------|
| | L02 | M25 × 1.5 | Φ11-15 | G3/4+ | 52 | 15 | 24 | 32 | CZ0227 2515 e202 |
| | L03 | M32 × 1.5 | Φ11-19 | G1" | 55 | 15 | 25 | 38 | CZ0227 3215 e203 |

订购规格 Order specifications:

 CZ0221 金属电缆密封套
 CZ0221 Metal cable glands

| 图样 Illustration | 编码 Code | 入口螺纹 Entry thread | 电缆直径 Cable diameter | SW | 螺纹长度 L1 Length of thread L1 | 长度 L2 Length L2 | 订购号 Order No. |
|--------------------|------------|----------------------|------------------------|----|--------------------------------|--------------------|-------------------------|
| | C03 | M25 × 1.5 | Φ8-17 | 32 | 15 | 33 | CZ0221 2515 e403 |
| | C04 | M32 × 1.5 | Φ12-21 | 37 | 16 | 39 | CZ0221 3216 e404 |

订购规格 Order specifications:

 CZ0226 增安型电缆密封套 (填料函)
 CZ0226 Increased safety cable glands (stopping boxes)

| 图样 Illustration | 编码 Code | 入口螺纹 Entry thread | 电缆直径 Cable diameter | | L | L1 | SW | 钢带厚度 C Armour wire thickness C | 订购号 Order No. |
|--------------------|------------|----------------------|---------------------|-----------|----|----|----|-----------------------------------|-------------------------|
| | | | A | B | | | | | |
| | G02 | M25 × 1.5 | 6-12.5 | 11.5-16 | 76 | 15 | 32 | 0.85 | CZ0226 2515 e002 |
| | G03 | M25 × 1.5 | 6.5-12.5 | 15-21 | 76 | 15 | 37 | 0.9 | CZ0226 2515 e003 |
| | G04 | M32 × 1.5 | 11-18.5 | 20.5-27.5 | 85 | 15 | 44 | 1.25 | CZ0226 3215 e004 |