

主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

China (PCEC Ex)	Ex de II C	GB3836 GB12476
IECEX	Ex de II C Gb	IEC60079
ATEX	⊕ II 2GD Ex de II C Gb	EN60079

 适用范围: 用于 1 区和 2 区
 使用环境温度: $-55^{\circ}\text{C} < \text{Ta} < 60^{\circ}\text{C}$

防护等级: IP20


额定电压: 最大输入电压 200VDC 或者额定功率, 取其中的最小值

额定功率: 0.1W

刻度: 0~100%

板前导轨型安装: 导轨 TS35 × 7.5 或螺钉固定

板后型安装: 在 1-6mm 面板上



Intended use: Can be used in zone 1 and zone 2

 Ambient temperature use: $-55^{\circ}\text{C} < \text{Ta} < 60^{\circ}\text{C}$

Degree of protection: Ip20

Rated voltage: 200VDC or power rating, whichever is smaller

Rated power: 0.1W

Scale: 0 ~ 100%

Board front mounting rail type mounting: May be held on mounting rails TS35 × 7.5 or with screws

Board back type mounting: On 1-6mm panel

P□/K□/L□/...系列操作头 P□/K□/L□/...Series operation head

China (PCEC Ex)	Ex e II	GB3836 GB12476
IECEX	Ex e II Ex tD A21	IEC60079
ATEX	⊕ II 2GD Ex e II Ex tD A21	EN60079

适用范围: 用于 1 区和 2 区, 21 区和 22 区

 使用环境温度: $-40^{\circ}\text{C} < \text{Ta} < 55^{\circ}\text{C}$

防护等级: IP66

材料: 聚酰胺

符合: CE 0575

Intended use: Can be used in zone 1 and zone 2

Can be used in zone 21 and zone 22

 Ambient temperature use: $-40^{\circ}\text{C} < \text{Ta} < 55^{\circ}\text{C}$

Degree of protection: IP66

Material: Polyamide

Conformity to: CE 0575

订购规格 Order specifications:

 板前导轨型 Board front mounting rail type	电阻值 Resistance value	订购号(编码) Order No.(Code)
	 板后型 Board back type	100 Ω 200 Ω 500 Ω 1000 Ω 2000 Ω 5000 Ω 10000 Ω 20000 Ω 50000 Ω 100000 Ω 200000 Ω 500000 Ω 1000000 Ω 2000000 Ω

6 — 板前导轨型 Board front mounting rail type
 7 — 板后型 Board back type

外形尺寸 Outline dimensions:
