

主要数据 Main technical data:

认证 Certification | 防爆标志 Ex mark | 符合标准 Meet the standard

China (PCEC Ex)	Ex e II DIP A21 TA	GB3836	GB12476
IECEX	Ex e II Ex tD A21	IEC60079	IEC61241
ATEX	Ex II 2 GD Ex e II Ex tD A21	EN60079	EN61241

适用范围: 用于 1 区和 2 区, 20 区, 21 区和 22 区

Intended use: Can be used in zone 1 and zone 2

 使用环境温度: $-40^{\circ}\text{C} < \text{Ta} < 55^{\circ}\text{C}$

Can be used in zone 20, zone 21 and zone 22

防护等级: IP66

 Ambient temperature: $-40^{\circ}\text{C} < \text{Ta} < 55^{\circ}\text{C}$

材料: 尼龙塑料

Degree of protection: IP66

Material: nylon plastic



订购规格 Order specifications:

图样 Illustration	编码 Code	入口螺纹 Entry thread	电缆直径 Diameter of cable	SW	螺纹长度 L1 Length of thread L1	长度 L2 Length L2	订购号 Order No.
 Ex-e CZ0220 e 电缆密封套 Cable gland	A01	M16 × 1.5	Φ4-9	20	10	27	CZ0220 1610 e101
	A02	M20 × 1.5	Φ5.5-13	24	11	31	CZ0220 2011 e102
	A03	M25 × 1.5	Φ8-17	29	11	36	CZ0220 2511 e103
	A04	M32 × 1.5	Φ12-21	36	12	43	CZ0220 3212 e104
	A05	M40 × 1.5	Φ17-28	46	14	47	CZ0220 4014 e105
	A06	M50 × 1.5	Φ22-35	55	16	54	CZ0220 5016 e106
	A07	M63 × 1.5	Φ27-48	68	16	57	CZ0220 6316 e107
	A08	M25 × 1.5	4 × Φ3 ~ Φ6 *	29	11	36	CZ0220 2511 e108
	A09	M32 × 1.5	4 × Φ5 ~ Φ7 *	36	12	43	CZ0220 3212 e109
	A10	M20 × 1.5	Φ5.5-13	24	16	31	CZ0220 2016 e110
	A11	M25 × 1.5	Φ8-17	29	16	36	CZ0220 2516 e111
	A12	M32 × 1.5	Φ12-21	36	16	43	CZ0220 3216 e112
	A13	M25 × 1.5	4 × Φ3 ~ Φ6 *	29	16	36	CZ0220 2516 e113
	A14	M32 × 1.5	4 × Φ5 ~ Φ7 *	36	16	43	CZ0220 3216 e114
 Ex-i CZ0220 i 电缆密封套 Cable gland	B01	M16 × 1.5	Φ4-9	20	10	27	CZ0220 1610 i101
	B02	M20 × 1.5	Φ5.5-13	24	11	31	CZ0220 2011 i102
	B03	M25 × 1.5	Φ8-17	29	11	36	CZ0220 2511 i103
	B04	M32 × 1.5	Φ12-21	36	12	43	CZ0220 3212 i104
	B05	M40 × 1.5	Φ17-28	46	14	47	CZ0220 4014 i105
	B06	M50 × 1.5	Φ22-35	55	16	54	CZ0220 5016 i106
	B07	M63 × 1.5	Φ27-48	68	16	57	CZ0220 6316 i107
	B08	M25 × 1.5	4 × Φ3 ~ Φ6 *	29	11	36	CZ0220 2511 i108
	B09	M32 × 1.5	4 × Φ5 ~ Φ7 *	36	12	43	CZ0220 3212 i109
	B10	M20 × 1.5	Φ5.5-13	24	16	31	CZ0220 2016 i110
	B11	M25 × 1.5	Φ8-17	29	16	36	CZ0220 2516 i111
	B12	M32 × 1.5	Φ12-21	36	16	43	CZ0220 3216 i112
	B13	M25 × 1.5	4 × Φ3 ~ Φ6 *	29	16	36	CZ0220 2516 i113
	B14	M32 × 1.5	4 × Φ5 ~ Φ7 *	36	16	43	CZ0220 3216 i114

外形尺寸 Outline dimensions:

注: * 多孔型 Multi-hole type


 单孔型
Single-hole type

 多孔型
Multi-hole type

附件 Accessories:

4024 专用扳手 Special spanner


 注: 4024 专用扳手专用于 CZ0220 电缆密封套。
 Note: The 4024 special spanner is used in the CZ0220 cable gland specially.

规格 Specifications	扳手宽度 Width of spanner	订购号 Order No.
M16	20	4024 / 20
M20	24	4024 / 24
M25	29	4024 / 29
M32	36	4024 / 36
M40	46	4024 / 46